

LY-650S LY-800S LY-1000S
















FULLY AUTOMATIC SIDE SEALING MACHINE FOR PP, OPP, BOPP, CPP, LDPE, HDPE.



Features

- High speed side sealing machine.
- Servo-driven feeding system with one set of photocell for printed bag.
- Human-machine interface for easy setting.
- Optional devices are available for almost all kinds of bags.

Bags available

 (1) Standard	 (2) Standard Lip	 (3) Gusset	 (4) Gusset Lip	 (5) Inside Lip A	 (6) Inside Lip B	 (7) Inside Lip C	 (8) Gusset inside Lip
 (9) Center Slit	 (10) Lip Slit	 (11) Outside Lip	 (12) Gusset out side Lip	 (13) Outside Lip	 (14) Outside Lip B	 (15) Outside Lip C	

Specification

Model	Bag Size		Production Speed (bags / Min)	Thickness of Film (mm)	Heaters	Power Required
	Width (m/m)	Length (m/m)				
LY-650S	75-800	75-650	60-200	0.01-0.10	2.6KW	4.3KW
LY-800S	75-800	75-800	60-200	0.01-0.10	2.6KW	4.7KW
LY-1000S	75-800	75-1000	60-200	0.01-0.10	3KW	5.0KW

Model	Machine dimensions			Machine Weight (kg)	Packing Size(kg)	Gross Weight (kg)	Air compressor (Not included)
	L(M)	W(M)	H(M)				
LY-650S	4.2	1.40	1.85	1700	3.0 x 1.5 x 200	2000	5HP
LY-800S	4.2	1.50	1.85	2000	3.0 x 1.7 x 200	2300	5HP
LY-1000S	4.2	2.00	1.85	2300	3.0 x 1.9 x 200	2600	5HP

Notes : due to continual research and improvement, mechanical specifications are subject to further revision without prior notice.